



AIRSTOP FLEX Sealing Plaster

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. AIRSTOP FLEX Sealing Plaster is tear-resistant with adhesive generously applied, and is suitable for a variety of bonding applications.

FIELD OF APPLICATION

- A quick seal for larger openings e.g. blow-in openings

ADVANTAGES

- quick and easy application
- strong adhesion

AVAILABLE IN THE FOLLOWING DIMENSIONS

Roll width	180	200
Pieces per roll	222	200
Rolls/carton	4	4

PRODUCT DATA

Composition	slightly expandable synthetic base material, laminated airtight, acrylate adhesive
Temperature resistance	- 40 °C - + 100 °C
Working temperature	from - 5 °C
UV-resistance	2 months
Storability	2 years; cool and dry
Colour	white transparent with Airstop imprint

GUIDELINES FOR USE

AIRSTOP FLEX Sealing Plaster

The materials used must be free from dust and grease and substrates must be dry and supporting. The greater the pressure applied, the better the performance of the adhesive tape.

AIRSTOP FLEX sealing Plaster has the function of sealant and not of a firm connector (No permanent tensile stresses may act on the bonded joints – e.g. if the drill cores of OSB boards are re-inserted, they must be mechanically fixed). The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is extremely resistant to ageing.



ISOCELL GmbH & Co KG
Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG
Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 544 47 20
office@isocell.ch

ISOCELL FRANCE
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË
Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB
Box 20059
161 02 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com