



# OMEGA N55 Adhesive

adhesive for wind and waterproof adhesion of acrylate or TPU-coated façades and underroof membranes, either to each other, or to connect with concrete, wood and metal.

## FIELD OF APPLICATION

- Adhesion at overlaps and joins for OMEGA UDO-s 330 and OMEGA facade membranes

## ADVANTAGES

- plasticizer-resistant
- resistant to oil, petrol, dilute acids and leach
- 1-component
- Adhesion on many substrates e.g. wood, concrete, metal

## AVAILABLE IN THE FOLLOWING DIMENSIONS

Package / Can	2,0 kg	4,5 kg
---------------	--------	--------

## PRODUKT DATA

Composition	nitrile rubber
Density	0,88 g/cm <sup>3</sup>
Working temperature	0 °C - + 40 °C
Coverage	40 g/m
Skin formation time dry/wet	10 min / 4 min
Storage	12 months unopened, room temperature
Colour	yellowish

10/2017\_EN

# ISOCELL

# GUIDELINES FOR USE OF OMEGA N55 Adhesive

**Wet bonding:** apply OMEGA N55 to one of the grease and dust-free surfaces. The sections can be joined during skin-forming time.

**Priming:** on difficult, porous or highly absorbent surfaces OMEGA N55 can also be used as a primer. For this purpose, apply a thin layer to the substrate — allow to air out for approx. 15 min. — then apply adhesive to the sheeting and apply pressure immediately.



ISOCELL GmbH  
Gewerbestraße 9  
5202 NEUMARKT AM WALLERSEE | Österreich  
Tel.: +43 6216 4108 | Fax: +43 6216 7979  
office@isocell.at

ISOCELL SCHWEIZ AG  
Herbergstrasse 29  
9524 ZUZWIL | Suisse /Schweiz  
Tel.: +41 71 544 47 20  
office@isocell.ch

ISOCELL FRANCE  
170 Rue Jean Monnet | ZAC de Prat Pip Sud  
29490 GUIPAVAS | France  
Tel.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99  
contact@isocell-france.fr

ISOCELL BUREEL BELGIË  
Außenborner Weg 1 | Schoppen  
4770 AMEL | Belgique  
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68  
office@isocell.be

ISOCELL Sverige AB  
Gamla Stallet | Stora Väsby  
194 37 UPPLANDS VÄSBY | Sverige  
Tel.: +46 10 130 25 01  
office@isocell.se

**ISOCELL**  
[www.isocell.com](http://www.isocell.com)