



## OMEGA UDO's CONDUIT SLEEVE

A pre-moulded accessory that can be used especially for fast and water-tight joins of standard pipe penetrations in combination with Omega UDOs 330 roofing membrane. Due to its elasticity and new universal size technology Omega UDOs provides a possibility to integrate conduits with sizes ranging from DN 90 to DN 125.

### APPLICATION

- Penetration points

### ADVANTAGES

- permanently elastic
- extremely flexible
- age-resistant
- stretchable
- for use from DN 90 to DN 125
- weldable and gluable

### AVAILABLE IN THE FOLLOWING DIMENSIONS

For penetration points of diameter	90 - 125 mm
Overall height	100 mm
Outer dimension	255 mm
Carton content / pcs.	10

### PRODUCT DATA

Composition	TPU
Temperature resistance	- 40 °C - + 100 °C
Weight	80g (± 10%)
Storage	cool and dry
Colour	dark grey

10.2017\_EN

**ISOCELL**

# PROCESSING GUIDELINES

## OMEGA UDO's CONDUIT SLEEVE

Pull Omega UDOs conduit sleeve over the pipe and lead to the Omega UDOs 330 roofing membrane. The base plate must be welded homogeneously to Omega UDOs 330 roofing membrane using N55 solution welding compound or a hot air gun.



ISOCELL GmbH  
Gewerbestraße 9  
5202 NEUMARKT AM WALLERSEE | Österreich  
Tel.: +43 6216 4108 | Fax: +43 6216 7979  
office@isocell.at

ISOCELL SCHWEIZ AG  
Herbergstrasse 29  
9524 ZUZWIL | Suisse /Schweiz  
Tel.: +41 71 544 47 20  
office@isocell.ch

ISOCELL FRANCE  
170 Rue Jean Monnet | ZAC de Prat Pip Sud  
29490 GUIPAVAS | France  
Tel.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99  
contact@isocell-france.fr

ISOCELL BUREEL BELGIË  
Außenborner Weg 1 | Schoppen  
4770 AMEL | Belgique  
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68  
office@isocell.be

ISOCELL Sverige AB  
Gamla Stallet | Stora Väsbys  
194 37 UPPLANDS VÄSBY | Sverige  
Tel.: +46 10 130 25 01  
office@isocell.se

**ISOCELL**  
[www.isocell.com](http://www.isocell.com)