



OMEGA UDOs external angle moulding

is a preformed section for use as a quick wind and water-tight join of outer corners in combination with OMEGA UDOs 330 roofing membrane.

APPLICATION

- Detailed solutions for external corners

ADVANTAGES

- vapour permeable
- heat and solvent weldable
- wind, rain and water-tight
- weldable and bondable

AVAILABLE IN THE FOLLOWING DIMENSIONS

Total width split	150 / 150 mm
Angled corner length	200 mm
Carton content / pcs.	20

PRODUCT DATA

Composition	PES spunbond fleece with TPU coating on both sides
Temperature resistance	- 40 °C - + 100 °C
Weight	64g (± 5%)
Resistance to water flow	W1
Storage	cool and dry
Colour	dark grey

GUIDELINES FOR USE

OMEGA UDOs external angle moulding is welded uniformly to the OMEGA UDOs 330 roofing membrane using solution welding compound, OMEGA N55 or heat gun.

12/2017_EN

ISOCELL GmbH
Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG
Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 544 47 20
office@isocell.ch

ISOCELL FRANCE
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tel.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË
Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB
Box 20059
161 02 BROMMA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com